


Name	10. CEILING: Exposed Attic Attached to Underside of Rafter																						
Date	04-20-2021																						
Section Schematic																							
Layers/R-values	<table border="1" data-bbox="418 531 1409 940"> <thead> <tr> <th data-bbox="418 531 862 646">Layer Name</th> <th data-bbox="862 531 1005 646">R-value of Assembly</th> <th data-bbox="1005 531 1157 646">R-value of Quattro Application</th> <th data-bbox="1157 531 1409 646">Notes</th> </tr> </thead> <tbody> <tr> <td data-bbox="418 646 862 695">Roof Deck (1/2" Plywood)</td> <td data-bbox="862 646 1005 695">0.79</td> <td data-bbox="1005 646 1157 695"></td> <td data-bbox="1157 646 1409 695">(1)</td> </tr> <tr> <td data-bbox="418 695 862 810">3.5" Air Gap</td> <td data-bbox="862 695 1005 810">2.05</td> <td data-bbox="1005 695 1157 810">2.05</td> <td data-bbox="1157 695 1409 810">(2) 3.5 Air Space @ 50/30 Horiz. Up (2.09+2.01)/2</td> </tr> <tr> <td data-bbox="418 810 862 894">QUATTRO Ultra-Thin Reflective Insulation</td> <td data-bbox="862 810 1005 894">1.63</td> <td data-bbox="1005 810 1157 894">1.63</td> <td data-bbox="1157 810 1409 894"></td> </tr> <tr> <td data-bbox="418 894 862 940"><b>Total</b></td> <td data-bbox="862 894 1005 940"><b>4.47</b></td> <td data-bbox="1005 894 1157 940"><b>3.68</b></td> <td data-bbox="1157 894 1409 940"></td> </tr> </tbody> </table>			Layer Name	R-value of Assembly	R-value of Quattro Application	Notes	Roof Deck (1/2" Plywood)	0.79		(1)	3.5" Air Gap	2.05	2.05	(2) 3.5 Air Space @ 50/30 Horiz. Up (2.09+2.01)/2	QUATTRO Ultra-Thin Reflective Insulation	1.63	1.63		<b>Total</b>	<b>4.47</b>	<b>3.68</b>	
Layer Name	R-value of Assembly	R-value of Quattro Application	Notes																				
Roof Deck (1/2" Plywood)	0.79		(1)																				
3.5" Air Gap	2.05	2.05	(2) 3.5 Air Space @ 50/30 Horiz. Up (2.09+2.01)/2																				
QUATTRO Ultra-Thin Reflective Insulation	1.63	1.63																					
<b>Total</b>	<b>4.47</b>	<b>3.68</b>																					
R-Value of Quattro Application	3.68 [h.ft <sup>2</sup> .F /Btu]																						
Notes/Reference	<ul data-bbox="467 1094 1419 1318" style="list-style-type: none"> <li>• Install QUATTRO perpendicular to rafters with a 2" overlap on the seams. Staple to the rafters at 2-3" intervals.</li> <li>• Leave gap of 2-3" on each side of the roof peak and within 18" on the lower edge of the roof line.</li> <li>• Seal the overlaps and joins with the special aluminum adhesive tape supplied by Aluthermo/Smartech.</li> </ul>																						